O300H.GL-GW1J.PVNV

Diffuse sensors with background suppression - hygiene

Article number: 11171769

Overview

- background suppression
- 30 ... 250 mm
- pulsed red laser diode
- push-pull
- Teach-in and IO-Link
- flylead connector M8, L=200 mm
- -10 ... 60 °C
- IP 68/69K & proTect+



Picture similar









Technical data	
General data	
Туре	Background suppression
Special type	Hygienic design
Light source	Pulsed red laser diode
Sensing distance Tw	30 250 mm
Sensing range Tb	15 250 mm
Repeat accuracy	< 0,1 mm at laser focus
Power on indication	LED green
Light indicator	LED yellow
Sensing distance adjust- ment	Teach-in and IO-Link
Laser class	1
Distance to focus	80 mm
Wave length	656 nm
Suppression of reciprocal influence	Yes
Alignment optical axis	< 2°
Approvals/certificates	Ecolab Adapted from EHEDG
Electrical data	
Response time / release time	< 0,25 ms

Electrical data	
Voltage supply range +Vs	11 30 VDC
Current consumption max. (no load)	30 mA
Current consumption typ.	25 mA
Voltage drop Vd	< 2,5 VDC
Output function	Light / dark operate
Output circuit	Push-pull
Output current	< 100 mA
Short circuit protection	Yes
Reverse polarity protection	Yes
Mechanical data	
Width / diameter	16,5 mm
Height / length	34,6 mm
Depth	28,7 mm
Туре	Rectangular
Housing material	Stainless steel 1.4404 (V4A)
Front (optics)	PMMA
Connection types	Flylead connector M8, L=200 mm
Ambient conditions	
Protection class	IP 68/69K & proTect+
Operating temperature	-10 +60 °C



O300H.GL-GW1J.PVNV


Diffuse sensors with background suppression - hygiene

Article number: 11171769

Remarks

- Magnetic Teach
- IO-Link: V1.1, filter functions, qTeach lock adjustable

Dimension drawing




• Cable length L = 200 mm

Laser warning


CLASS 1 LASER PRODUCT

IEC 60825-1/2014
Complies with 21 CFR 1040.10 and 1040.11 except for conformance with IEC 60825-1 Ed. 3., as described in Laser Notice No. 56, dated May 8, 2019

Connection diagram



Pin assignment



Beam characteristic (typically)

